

CORNER STEADIES

When rigid stability is required the AL-KO range of stands fits the bill. Available in varying heights and also in weld on swivel bracket versions. These steady stands are ideal for fixed location stabilizing of trailers and plant equipment.

654859



Description

Corner steady drop down 590mm, fitted with Big foot

Specifications

Surface Finish:	Zinc plated
Closed length:	410mm
Open Length:	590mm

654874



Description

Corner steady drop down 740mm, fitted with Big foot

Specifications

Surface Finish:	Zinc plated
Closed length:	510mm
Open Length:	740mm

654884



Description

Corner steady drop down 840mm, fitted with Big foot

Specifications

Surface Finish:	Zinc plated
Closed length:	610mm
Open Length:	840mm

654859B



Description

Corner steady drop down 590mm, fitted with Big foot

Specifications

Surface Finish:	E Coat, Black
Closed length:	410mm
Open Length:	590mm

654874B



Description

Corner steady drop down 740mm, fitted with Big foot

Specifications

Surface Finish:	E Coat, Black
Closed length:	510mm
Open Length:	740mm

654884B



Description

Corner steady drop down 840mm, fitted with Big foot

Specifications

Surface Finish:	E Coat, Black
Closed length:	610mm
Open Length:	840mm

654874AL



Description

Corner steady drop down 740mm, fitted with large ant free aluminium foot

Specifications

Surface Finish:	Zinc plated
Closed length:	510mm
Open Length:	740mm

654500



Description
Corner steady hex drive 500mm.
No wheel.

Specifications

Surface Finish:	Zinc plated
Mounting Type:	Side bolt
Mounting Spacing:	250mm
Slot Size:	14mm x 10mm

654500G



Description
Corner steady hex drive 500mm.
No wheel.

Specifications

Surface Finish:	Galvanised
Mounting Type:	Top bolt
Mounting Spacing:	750mm x 25
Hole Size:	6mm

654530



Description
Rear, corner steady hex drive 500mm.
With wheel

Specifications

Surface Finish:	Zinc plated
Mounting Type:	Side bolt
Mounting Spacing:	250mm
Slot Size:	14mm x 10mm

654555GBF



Description
Corner steady 500mm, fitted with Big foot.
No wheel

Specifications

Surface Finish:	Galvanised
Mounting Type:	Side bolt
Mounting Spacing:	250mm
Slot Size:	14mm x 10mm

654600



Description
Front, corner steady hex drive 600mm.
No wheel

Specifications

Surface Finish:	Zinc plated
Mounting Type:	Side bolt
Mounting Spacing:	250mm
Slot Size:	14mm x 10mm

654630



Description
Rear, corner steady hex drive 600mm.
With wheel

Specifications

Surface Finish:	Zinc plated
Mounting Type:	Side bolt
Mounting Spacing:	250mm
Slot Size:	14mm x 10mm

654701G



Description
Corner steady hex drive 700mm.

Specifications

Surface Finish:	Galvanised
Mounting Type:	Top bolt
Mounting Spacing:	750mm x 25mm
Hole Size:	6mm

654701



Description
Corner steady hex drive 700mm.

Specifications

Surface Finish:	Zinc plated
Mounting Type:	Side bolt
Mounting Spacing:	250mm
Slot Size:	14mm x 10mm

655410



Description
Corner steady AL-KO 1000 kg
(Euro style)