

AL-KO LOCKABLE COUPLINGS ADDED PROTECTION

**FEATURING
AL-KO XL GRIP**



Fixed



2T Over ride



3.5T Fixed (suits electric brake)



3.5T Fixed with park (suits electric brake)

The new range of premium AL-KO lockable couplings are designed to ensure your caravan or trailer is secure, and eliminates the need to purchase and fit a separate coupling lock.

The coupling can be locked to provide theft protection both when hitched - to prevent disconnection and also when unhitched - to prevent connection to a tow vehicle.

AL-KO lockable couplings are designed to suit a standard 50mm tow ball making it a convenient option for boat trailers, box trailers, caravans, camper trailers & horse floats.

The addition of the new AL-KO XL Grip also enhances comfort and ease of use.



Lock is integrated into the coupling body



XL Grip for optimal ergonomics + ease of use compared to classic design.



AL-KO standard mounting options for an easy swap over.



Each coupling comes with 2 keys.

AL-KO Lockable coupling Range.



614065LPL
2T Fixed



614054LPL
2T Over ride



614015L
3.5T Fixed



614015LPBWCA
3.5T Fixed with park

	614065LPL	614054LPL	614015L & 614015LPBWCA
Capacity (ATM*)	2000 kg	2000 kg	3500 kg
Suits Braking System	Non braked	Over run Hydraulic & Over run Mechanical	Electric & Power assisted
Mounting Pattern (hole centres)	2 bolt - 102mm 3 bolt - 111mm x 51mm	4 bolt - 184mm x 54mm	4 bolt - 182.5mm x 55mm
Bolt Hole Size	13.5mm	13.5mm	13.5mm
Recommended Bolt Size	10mm	12mm	12mm
Recommended Bolt Grade	Grade A4-80	Grade A4-80	Grade A4-80
Supporting Products		3/4" Hydraulic conversion plate 610943. 7/8" Hydraulic conversion plate 610944. Mechanical conversion plate 614053.	

Note: For Imperial bolt sizes or socket head cap screws must be equivalent or higher strength than those listed above. Please check with your bolt supplier for availability and suitability.

Due to the often harsh vibrations sustained at axle mounts, AL-KO recommends the use of anti-loose or nyloc nuts.